

```

## PLOTTING XEOL Maps ##
XEOLMap = XEOLMapper()

## LOADING/ADDING/SUBTRACTING 2-D XEOL DATA FROM A FILE ##
## Loads 2-D XES scans data from HDF5 file
XEOLMap.load(config, 'filename', 'detector', arg, **kwargs)
## args = scan number to be loaded

## Loads and sums 2-D XEOL scans data from HDF5 file
XEOLMap.add(config, 'filename', 'detector', *args, **kwargs)
## *args = comma seperated list of scans to be plotted or added and then plotted

## Loads and subtracts 2-D XEOL scans data from HDF5 file
XEOLMap.subtract(config, 'filename', 'detector', *args, **kwargs)
## *args = s1, p1 -> The data from p1 is subtracted from s1
## *args = [s1, ..., sn], [p1, ..., pn] -> The sum of p1..pn is subtracted from the sum of s1..sn

## Loads and stitches 2-D XEOL scans data from HDF5 file
XEOLMap.stitch(config, 'filename', 'detector', *args, **kwargs)
## *args = comma seperated list of scans to be stitched

## Loads and subtracts the background from each image column
XEOLMap.background_1d(config, 'filename', 'detector', *args, **kwargs)
## *args = s1 -> The scan to be subtracted from all previous load/add/subtract actions
## *args = [s1, ..., sn] -> The sum of scans s1..sn to be subtracted from all previous load/add/subtract

## Loads and subtracts the image the loaded image
XEOLMap.background_2d(config, 'filename', 'detector', *args, **kwargs)
## *args = s1 -> The scan to be subtracted from all previous load/add/subtract actions
## *args = [s1, ..., sn] -> The sum of scans s1..sn to be subtracted from all previous load/add/subtract

## REQUIRED VARIABLES ##
## config = RIXS -> RIXS Endstation
## config = RSXS -> RSXS Endstation
## filename = hdf5 file -> Extension .h5 not needed
## detector -> MCA type detector
## NOTE: Simple math allowed with xes_stream with constants and variables, i.e. +, -, /, *

## *kwargs options ##
## norm = True -> Scales the data such that its range is 0 to 1.
## xoffset = [(S1,P1),..., (SN,PN)] -> Adjusts x-axis scale to map SN to PN
## xoffset = value -> Shifts x-axis scale by a constant value
## yoffset = [(S1,P1),..., (SN,PN)] -> Adjusts y-axis scale to map SN to PN
## yoffset = value -> Shifts y-axis scale by a constant value
## grid_x = [start, stop, delta] -> Change x-axis grid to be uniform
## grid_y = [start, stop, delta] -> Change y-axis grid to be uniform
## binsize_x = bins -> Bins data along x-axis, specify the number of points (extra points removed)
## binsize_y = bins -> Bins data along y-axis, specify the number of points (extra points removed)

## SET RANGE OF Y and X VALUES ##
XEOLMap.xlim(min, max)
XEOLMap.ylim(min, max)

# PLOTTING SCAN DATA ##
XEOLMap.plot(**kwargs)

## **kwargs ##
## title = 'New Title of plot' -> Replaces default title with user defined
## xlabel = 'x-axis label' -> Replaces default x-axis label with user defined
## ylabel = 'y-axis label' -> Replaces default y-axis label with user defined
## xlabel = 'colorscale label' -> Replaces default colorscale label with user defined
## plot_height = value -> The plot height in points, default is 600
## plot_width = value -> The plot width in points, default is 900
## norm = True -> Normalizes all the data between 0 and 1
## vmin = value -> Sets the maximum value of the colorscale
## vmax = value -> Sets the minimum value of the colorscale

## EXPORTING PLOT DATA ##
XEOLMap.export('filename', **kwargs)

# REQUIRED VARIABLES ##
## filename = filename to be used for ASCII file, do not add extension
## NOTE: Data is exported as it displayed, only options in plotting methods are ignored.

## **kwargs ##
## split_files = True -> Saves each data stream with number appended to the filename

```

```
## XEOL Map with Background Subtracted
```

```
XEOLMap = XEOLMapper()
```

```
XEOLMap.load(RIXS, 'HDF5_Notebook', 'XEOL', 14)
```

```
XEOLMap.background_1d(RIXS, 'HDF5_Notebook', 'XEOL/50', 16)
```

```
XEOLMap.plot(norm = True)
```

```
XEOLMap.export('XEOL_Map')
```

